

1 CAT 6 U/UTP



Standarts

TECHNICAL SPECIFICATIONS

|                        | UTP CAT 5E PLUG                                                                            |
|------------------------|--------------------------------------------------------------------------------------------|
| Housing Material       | PC                                                                                         |
| UL Flammability Rating | Polyolefin                                                                                 |
| Contact Material       | Copper Brass                                                                               |
| Contact Gold Plating   | FU/3U/50U(Normally 50U)                                                                    |
| Prong Type             | 3 Prongs                                                                                   |
| Inner Wire             | 1.0mm(Normally)/0.9mm/0.8mm/0.75mm                                                         |
| Color                  | Normally transparent color with MOQ 5,000PCS, other color are available with MOQ 50,000PCS |
| Package                | Normally 1,000pcs/tray, 10,000pcs/carton Carton Size: 43.5*34.5*29.0 cm                    |

ELECTRICAL AND MECHANICAL CHARACTERISTICS

|                                  | CAT 6A S/FTP                   |
|----------------------------------|--------------------------------|
| Rated Current                    | 125V AC, 1.5A@25C              |
| Contact Resistance:              | 20mOhm Max.                    |
| Insulation Resistance            | 500mOhm min, 100V DC/min.      |
| Voltage Proof                    | 1000V AC/1 minute no breakdown |
| insertion Force&Withdrawal Force | 30N Max."                      |
| Durability                       | 750 cycles Min.                |